



## EV AP 560 - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



CERAMICS AND POTTERY INDUSTRIES



WINE



- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Extractable collection container with optional use of disposable bags
- ✓ High air flow value
- ✓ Full customization for specific needs
- ✓ Conceived for the suction of fine dusts suspended in the air
- ✓ Optional articulated arm to suction in a restricted area



### UNITÀ ASPIRANTE

Voltage	V - Hz	400 - 50
Power	kW	4
Electrical protection	IP	55
Max waterlift	mmH2O	200 / 300 / 350
Max air flow	m <sup>3</sup> /h	2700 / 1800 / 1100
Suction inlet	mm	200 / 150 / 120
Noise level (EN ISO 3744)	dB(A)	74



### UNITÀ FILTRANTE

Filter Type		Star
Surface - Diameter	cm <sup>2</sup> -mm	50.000-500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Cleaning system		Manual



### UNITÀ DI RACCOLTA

Discharge system		Roll-out container
Capacity	lt.	100



### INGOMBRI

Dimensions	cm	75x85x250h
Weight	kg	130



## UNITÀ ASPIRANTE

The suction unit is made of an electric fan which guarantees elevated air flow.



## UNITÀ FILTRANTE

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



## UNITÀ DI RACCOLTA

The detachable steel collection tank has a quick release system for the rapid disposal of the sucked material.



## OPTIONALS

- ✓ FILTER FOR FINE DUST - CLASS M
- ✓ ANTISTATIC FILTER CLASS M
- ✓ ANTISTATIC FILTER CLASS L
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ EXTRACTION ARM
- ✓ DOUBLE EXTRACTION ARM