



EV AP 560 - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



CERAMICS AND POTTERY INDUSTRIES



WINE



- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Extractable collection container with optional use of disposable bags
- ✓ High air flow value
- ✓ Full customization for specific needs
- ✓ Conceived for the suction of fine dusts suspended in the air
- ✓ Optional articulated arm to suction in a restricted area



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	4
Electrical protection	IP	55
Max waterlift	mmH ₂ O	200 / 300 / 350
Max air flow	m ³ /h	2700 / 1800 / 1100
Suction inlet	mm	200 / 150 / 120
Noise level (EN ISO 3744)	dB(A)	74



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	50.000-500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Cleaning system		Manual



COLLECTION UNIT

Discharge system		Roll-out container
Capacity	lt.	100



VOLUME

Dimensions	cm	75x85x250h
Weight	kg	130



SUCTION UNIT

The suction unit is made of an electric fan which guarantees elevated air flow.



FILTER UNIT

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The detachable steel collection tank has a quick release system for the rapid disposal of the sucked material.



OPTIONALS

- ✓ FILTER FOR FINE DUST - CLASS M
- ✓ ANTISTATIC FILTER CLASS M
- ✓ ANTISTATIC FILTER CLASS L
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ EXTRACTION ARM
- ✓ DOUBLE EXTRACTION ARM